


FYSH-3014

No	Part No	Wavelength(nm) Color Temp(K)	Number of LEDs	Voltage (V DC)	Power(W)	Radiance Angle(°)	Luminous Flux (Lm)	Operation Temperatur e	width (mm)	Protection level
1	FYSH-3014UWC-60-12V-NW4	2700~6500	60	12	04. Aug	120	480	-30~+60°C	4	IP20
2	FYSH-3014UWC-60-12V-WW4	2700~6500	60	12	04. Aug	120	480	-30~+60°C	4	Nano
3	FYSH-3014UWC-120-12V-NW4	2700~6500	120	12	09. Jun	120	960	-30~+60°C	4	IP20
4	FYSH-3014UWC-120-12V-WW4	2700~6500	120	12	09. Jun	120	960	-30~+60°C	4	Nano
5	FYSH-3014UWC-198-12V-NW4	2700~6500	198	12	15.84	120	1584	-30~+60°C	4	IP20
6	FYSH-3014UWC-198-12V-WW4	2700~6500	198	12	15.84	120	1584	-30~+60°C	4	Nano
7	FYSH-3014UWC-128-24V-NW10	2700~6500	128	24	15	120	1950	-40~+60°C	10	IP20
8	FYSH-3014UWC-128-24V-WW10	2700~6500	128	24	15	120	1950	-40~+60°C	10	Nano
9	FYSH-3014UWC-192-24V-NW10	2700~6500	192	24	24	120	2600	-40~+60°C	10	IP20
10	FYSH-3014UWC-192-24V-WW10	2700~6500	192	24	24	120	2600	-40~+60°C	10	Nano
11	FYSH-3014UWC-240-24V-NW10	2700~6500	240	24	25	120	3250	-40~+60°C	10	IP20
12	FYSH-3014UWC-240-24V-WW10	2700~6500	240	24	25	120	3250	-40~+60°C	10	Nano


FYSH-2835

No	Part No	Wavelength(nm) Color Temp(K)	Number of LEDs	Voltage (V DC)	Power(W)	Radiance Angle(°)	Luminous Flux (Lm)	Operation Temperatur e	width (mm)	Protection level
1	FYSH-2835UWC-120-24V-NW5	2700~6500	120	24	28. Aug	120	2880	-30~+60°C	5	IP20
2	FYSH-2835UWC-120-24V-WW5	2700~6500	120	24	28. Aug	120	2880	-30~+60°C	5	Nano
3	FYSH-2835UWC-128-24V-NW10	2700~6500	128	24	25	120	2500	-40~+60°C	10	IP20
4	FYSH-2835UWC-128-24V-WW10	2700~6500	128	24	25	120	2500	-40~+60°C	10	Nano
5	FYSH-2835UWC-192-24V-NW10	2700~6500	192	24	35	120	3500	-40~+60°C	10	IP20
6	FYSH-2835UWC-192-24V-WW10	2700~6500	192	24	35	120	3500	-40~+60°C	10	Nano
7	FYSH-2835UWC-240-24V-NW10	2700~6500	240	24	45	120	4500	-40~+60°C	10	IP20
8	FYSH-2835UWC-240-24V-WW10	2700~6500	240	24	45	120	4500	-40~+60°C	10	Nano


FYSH-3528

No	Part No	Wavelength(nm) Color Temp(K)	Number of LEDs	Voltage (V DC)	Power(W)	Radiance Angle(°)	Luminous Flux (Lm)	Operation Temperatur e	width (mm)	Protection level
1	FYSH-3528UWC-60-24V-NW8	2700~6500	60	24	4,8	120	480	-30~+60°C	8	IP20
2	FYSH-3528UWC-60-24V-WW8	2700~6500	60	24	4,8	120	480	-30~+60°C	8	IP67/Nano
3	FYSH-3528UWC-90-24V-NW8	2700~6500	90	24	8,64	120	780	-30~+60°C	8	IP20
4	FYSH-3528UWC-90-24V-WW8	2700~6500	90	24	8,64	120	780	-30~+60°C	8	IP67/Nano
5	FYSH-3528UWC-120-24V-NW8	2700~6500	120	24	9,6	120	960	-30~+60°C	8	IP20
6	FYSH-3528UWC-120-24V-WW8	2700~6500	120	24	9,6	120	960	-30~+60°C	8	IP67/Nano

7	FYSH-3528UWC-144-24V-NW10	2700-6500	144	24	11,52	120	1150	-30~+60°C	10	IP20
8	FYSH-3528UWC-144-24V-WW10	2700-6500	144	24	11,52	120	1150	-30~+60°C	10	IP67/Nano
9	FYSH-3528UWC-240-24V-NW10	2700-6500	240	24	19,2	120	1920	-30~+60°C	10	IP20
10	FYSH-3528UWC-240-24V-WW10	2700-6500	240	24	19,2	120	1920	-30~+60°C	10	IP67
11	FYSH-3528UWC-64-24V-NW10-HL	2700-6500	64	24	4	120	520	-40~+60°C	10	IP20
12	FYSH-3528UWC-64-24V-WW10-HL	2700-6500	64	24	4	120	520	-40~+60°C	10	IP67/Nano
13	FYSH-3528UWC-128-24V-NW10-HL	2700-6500	128	24	7	120	910	-40~+60°C	10	IP20
14	FYSH-3528UWC-128-24V-WW10-HL	2700-6500	128	24	7	120	910	-40~+60°C	10	IP67/Nano
15	FYSH-3528UWC-192-24V-NW10-HL	2700-6500	192	24	10,8	120	1400	-40~+60°C	10	IP20
16	FYSH-3528UWC-192-24V-WW10-HL	2700-6500	192	24	10,8	120	1400	-40~+60°C	10	IP67
17	FYSH-3528UWC-240-24V-NW10-HL	2700-6500	240	24	14	120	1820	-40~+60°C	10	IP20
18	FYSH-3528UWC-240-24V-WW10-HL	2700-6500	240	24	14	120	1820	-40~+60°C	10	IP67
19	FYSH-3528XXC-64-24V-NW10	Pink 2000±100K	64	24	7	120	700	-30~+60°C	10	IP20
		Amber 2300±100K					840			
		White 5500±200K					910			
20	FYSH-3528XXC-128-24V-NW10	Pink 2000±100K	128	24	14	120	1400	-30~+60°C	10	IP20
		Amber 2300±100K					1680			
		White 5500±200K					1820			
21	FYSH-3528XXC-192-24V-NW10	Pink 2000±100K	192	24	22	120	1980	-30~+60°C	10	IP20
		Amber 2300±100K					2200			
		White 5500±200K					2420			
22	FYSH-3528XXC-240-24V-NW10	Pink 2000±100K	240	24	28,8	120	2380	-30~+60°C	10	IP20
		Amber 2300±100K					2660			
		White 5500±200K					2800			
23	FYSH-3535RGBC-60-12V-NW6	623±5	60	12	4,8	120	120	-30~+60°C	6	IP20
		520±5			4,8		240			
		465±5			4,8		60			
24	FYSH-3535RGBC-120-24V-NW10	623±5	120	24	9,6	120	240	-30~+60°C	10	IP20
		520±5			9,6		480			
		465±5			9,6		120			



FYSH-5050

No	Part No	Wavelength(nm) Color Temp(K)	Number of LEDs	Voltage (V DC)	Power(W)	Radiance Angle(°)	Luminous Flux (Lm)	Operation Temperature	width (mm)	Protection level
1	FYSH-5050UW3C-30-24V-NW10	2700-6500	30	24	8,64	120	780	-30~+60°C	10	IP20
2	FYSH-5050UW3C-30-24V-WW10	2700-6500	30	24	8,64	120	780	-30~+60°C	10	IP67
3	FYSH-5050UW3C-60-24V-NW10	2700-6500	60	24	14,4	120	1400	-30~+60°C	10	IP20
4	FYSH-5050UW3C-60-24V-WW10	2700-6500	60	24	14,4	120	1400	-30~+60°C	10	IP67
5	FYSH-5050RGBC-30-24V-NW10	623±5	30	24	2,88	120	60	-30~+60°C	10	IP20
		520±5			2,88		150			

6	FYSH-5050RGBC-30-24V-WW10	465±5	30	24	2,88	120	35	-30~+60°C	10	IP67
		623±5			2,88		60			
		520±5			2,88		150			
		465±5					35			
7	FYSH-5050RGBC-60-24V-NW10	623±5	60	24	4,8	120	120	-30~+60°C	10	IP20
		520±5			4,8		300			
		465±5			4,8		70			
8	FYSH-5050RGBC-60-24V-WW10	623±5	60	24	4,8	120	120	-30~+60°C	10	IP67
		520±5			4,8		300			
		465±5			4,8		70			
9	FYSH-5050RGBWC-60-24V-NW10	623±5	60	24	4,8	120	120	-30~+60°C	10	IP20
		520±5			4,8		300			
		465±5			4,8		70			
		3000±150K			4,8		360			
10	FYSH-5050RGBWC-60-24V-WW10	623±5	60	24	4,8	120	120	-30~+60°C	10	IP67
		520±5			4,8		300			
		465±5			4,8		70			
		3000±150K			4,8		360			