

FYLM-2835


No	Part No	Wavelength(nm) Color Temp(K)	Number of LEDs	Voltage (V DC)	Power(W)	Radiance Angle(°)	Luminous Flux (Lm)	Operation Temperature	Dimension:(mm)	Protection level
1	FYLM-2835UW4242W-04-12V-XX-01	2800~14000	4	12	Jan 44	120	140	-20~+60°C	42.00*42.00*7.50	IP67
2	FYLM-2835UW7617W-03-12V-XX-01	2800~14000	3	12	01. Mai	120	130	-20~+60°C	75.70*16.70*4.80	IP67

FYLM-5050


No	Part No	Wavelength(nm) Color Temp(K)	Number of LEDs	Voltage (V DC)	Power(W)	Radiance Angle(°)	Luminous Flux (Lm)	Operation Temperature	Dimension:(mm)	Protection level
1	FYLM-5050UW6540W-06-12V-XX-01	3000~12000	6	12	1,44	120	110	-20~+60°C	65.00*40.00*9.50	IP67
2	FYLM-5630UW6415W-03-12V-XX-01	2800~14000	3	12	1,32	120	120	-20~+60°C	64.00*15.00*5.00	IP67
3	FYLM-5050RGB3434W-03-12V-01	620~640	3	12	0.72	120	4	-20~+60°C	34.00*34.00*7.00	IP65
		515~530			0.72		10			
		465~472.5			0.72		4			
4	FYLM-5050RGB6540W-06-12V-01	620~640	6	12	1,5	120	8	-20~+60°C	65.00*40.00*9.50	IP67
		515~530			1,5		20			
		465~472.5			1,5		8			

For further information, data-sheets and samples you are welcome to contact us